

# CORKLIFE CORKPARQUET

Technical Data Sheet – Cork Parquet for glue-down installation

Properties	Standard-Test Method	Unit	Value
Level of use Domestic	EN 685	Class	23
Level of use Commercial	EN 685	Class	32
<b>General Properties EN 12104</b>			
Dimensions	EN 427/EN 428	mm	300 x 300 x 4 / 600 x 300 x 4
Raw density	EN 672	kg/m <sup>3</sup>	< 500
Mass per unit area	EN 430	g/m <sup>2</sup>	8000
<b>Safety Properties</b>			
Fire resistance	EN 13501-1	Class	Efl s1
Electrical behaviour	EN 1815	Class	antistatic
<b>Optional Properties</b>			
Impact sound reduction	ISO 140-8	dB	16
Thermal resistance	EN 12667	m <sup>2</sup> K/W	0,07
Formaldehyde emission	DIN EN 717-1/2	mg/m <sup>3</sup> Class	< 0,01 E1
Content pentachlorophenol (PCP)	CEN/TR 14823 (ihd-W 409)	Classification	PCP free



**CORKPARQUET - NATURAL, WAXED OR SEALED**

**CORKPARQUET SURFACE**  
natural, waxed or pre-sealed

**DECORATIVE CORK VENEER**  
naturally beautiful designs

**PRESSED CORK BASE**  
flexible, isolating cork layer for high walking and standing comfort



[www.blauer-engel.de/uz120](http://www.blauer-engel.de/uz120)



- 1) Apply at least 3-4 layers of CL varnish after installation.
- 2) Treat with standard oil/wax care after installation.
- 3) Apply at least 1-2 layers of CL varnish after installation.